



8165 E Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Report No: L011705701



Report No: L011705701

Issue Date: 2/9/2017

Prepared For: Vantage Lighting
181 Narragansett Park Drive, E Providence, RI 2961

Model Number: A4V0FLED-2035K

Test: Photometric/Electrical Test

Standards Used: Appropriate part or all test guidelines were used for test performed:
IESNA LM79: 2008 Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products
ANSI NEMA ANSLG C78.377: 2008 Specification of the Chromaticity of Solid State Lighting Products
ANSI C82.77:2002: Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

Description of Sample: Client submitted the sample. Received in working and undamaged condition. No modifications were necessary.

Testing Condition: Fixture is tested with no special conditions.

Sample Arrival Date: 2/1/17

Date of Tests: 2/6/17 - 2/9/17

Seasoning of Sample: No seasoning was performed in accordance with IESNA LM-79.

Equipment List

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S1	11/28/17
ITECH	IT6122	PS-DC03-S1	11/28/17
Fluke Digital Thermometer	52k/J	MT-TP02-GC	11/28/17
LLI Type C Goniophotometer System	RMG-C-MKII	CD-LL04-GC	--
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Test Summary

Manufacturer:	Vantage Lighting
Model Number:	A4V0FLED-2035K
Driver Model Number:	PHILIPS ADVANCE XI025C070V054DSM1
Total Lumens:	2259.94
Input Voltage (VAC/60Hz):	120.00
Input Current (Amp):	0.21
Input Power (W):	25.30
Input Power Factor:	0.99
Current ATHD @ 120V(%):	9%
Current ATHD @ 277V(%):	N/A
Efficacy:	89
Ambient Temperature (°C):	25.0
Stabilization Time (Hours):	1:25
Total Operating Time (Hours):	2:05
Off State Power(W):	0.00




FIG.1 LUMINAIRE

*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Test Methods

Photometric Measurements - Goniophotometer

A Custom Light Laboratory Type C Rotating Mirror Goniophotometer was used to measure candelas(intensity) at each angle of distribution as defined by IESNA for the appropriate fixture type.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Disclaimers:

This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of Federal Government.

Report Prepared by : Keyur Patel

Test Report Released by:



Jeff Ahn
Engineering Manager

Test Report Reviewed by:



Steve Kang
Quality Assurance

**Attached are photometric data reports. Total number of pages: 8*



8165 E. Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Photometric Test Report

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L011705701.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] L011705701
[TESTLAB] LIGHT LABORATORY, INC.
[ISSUEDATE] 2/9/2017
[MANUFAC] VANTAGE LIGHTING
[LUMCAT] A4V0FLED-2035K
[LUMINAIRE] RECESSED DOWNLIGHT
[BALLASTCAT] PHILIPS ADVANCE XI025C070V054DSM1
[LAMPPOSITION] 0,0
[LAMPCAT] N/A
[OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
[MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
[INPUT] 120VAC, 25.30W
[TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2260
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	89
Total Luminaire Watts	25.3
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.00
Spacing Criterion (90-270)	1.00
Spacing Criterion (Diagonal)	0.94
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.35 ft (Diameter)
Luminous Width (90-270)	0.35 ft (Diameter)
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	29006	29006	29006
55	1754	1754	1754
65	1587	1587	1587
75	2159	2159	2159
85	5130	5130	5130

CANDELA TABULATION

	<u>0</u>
0.0	2254
1.0	2251
3.0	2243
5.0	2233
7.0	2221
9.0	2203
11.0	2175
13.0	2136
15.0	2088
17.0	2030
19.5	1944
22.5	1809
25.5	1637
29.0	1392
33.0	1033
37.5	601
42.5	288
47.5	79
55.0	9
65.0	6
75.0	5
85.0	4
90.0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L011705701.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	760.92	N.A.	33.70
0-30	1478.78	N.A.	65.40
0-40	1985.28	N.A.	87.80
0-60	2241.22	N.A.	99.20
0-80	2253.99	N.A.	99.70
0-90	2259.94	N.A.	100.00
10-90	2087.78	N.A.	92.40
20-40	1224.36	N.A.	54.20
20-50	1452.1	N.A.	64.30
40-70	263.05	N.A.	11.60
60-80	12.77	N.A.	0.60
70-80	5.66	N.A.	0.30
80-90	5.95	N.A.	0.30
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	2259.94	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	172.16
10-20	588.76
20-30	717.86
30-40	506.50
40-50	227.74
50-60	28.20
60-70	7.11
70-80	5.66
80-90	5.95
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : L011705701.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0	
	RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	0
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93	0
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	86	0
3	101	95	89	85	99	93	88	85	91	87	83	88	85	82	86	83	81	79	0
4	96	88	82	78	94	87	81	77	85	80	76	83	79	75	81	77	75	73	0
5	91	82	76	71	89	81	75	71	79	74	70	77	73	70	76	72	69	67	0
6	86	76	70	66	84	76	70	65	74	69	65	73	68	64	71	67	64	63	0
7	81	71	65	61	80	71	65	61	69	64	60	68	63	60	67	63	60	58	0
8	77	67	61	56	76	66	60	56	65	60	56	64	59	56	63	59	55	54	0
9	73	63	57	52	72	62	56	52	61	56	52	60	56	52	60	55	52	50	0
10	69	59	53	49	68	59	53	49	58	53	49	57	52	49	56	52	49	47	0

POLAR GRAPH



Maximum Candela = 2254 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)